

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : G09G 3/30	A1	(11) International Publication Number: WO 93/23842 (43) International Publication Date: 25 November 1993 (25.11.93)
(21) International Application Number: PCT/US93/04698 (22) International Filing Date: 17 May 1993 (17.05.93) (30) Priority data: 07/886,214 21 May 1992 (21.05.92) US (71) Applicant: MOTOROLA, INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US). (72) Inventors: McLAUGHLIN, Kevin, Thomas ; 7420 Woodland Ck. Ln., Lake Worth, FL 33467 (US). PARKES, John, Joseph ; 742 Rider Road, Boynton Beach, FL 33435 (US). (74) Agents: KOCH, William, E. et al.; Motorola, Inc., Intellectual Property Dept, 1500 N.W. 22nd Avenue, Boynton Beach, FL 33426-8292 (US).	(81) Designated States: CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: COMBINATION DISPLAY BACKLIGHT AND LIGHT SENSOR



(57) Abstract

A display device (20) comprises a display (21) for displaying information and an electrochromic panel (22) located contiguous to the display for sensing ambient light and lighting the display when the ambient light is below a threshold.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LI	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

COMBINATION DISPLAY BACKLIGHT AND LIGHT SENSOR

Field of the Invention

5 This invention relates in general to information displays, and more particularly to displays having a backlight for improving the visibility of information presented on the display.

Background of the Invention

10

Visual displays for presenting information exist in several known devices such as calculators, watches, and selective call receivers. Conventionally, the display comprises a liquid crystal display (LCD) that may be selectively programmed to display the information. Typically, the display includes either a reflective element contiguous to the display for reflecting light or a backlight mechanism for providing light through the display to improve the readability of the information. Still some previously known electronic devices having displays have included a light sensor separate from the display for enabling the backlight mechanism in low ambient light conditions.

20

However, the light sensor requires additional space on the electronic device housing the display and may cause environmental problems by allowing dust, humidity, etc. access to the circuitry.

25

Summary of the Invention

A display device comprises a display for displaying information and an electroluminescent panel located contiguous to the display for sensing ambient light and lighting the display when the ambient light is below a threshold.

30

Brief Description of the Drawings

FIG. 1 is a block diagram of a previously known selective call receiver.

35

FIG. 2 is a cross section of a visual display and electroluminescent panel in accordance with an embodiment of the present invention.

FIG. 3 is a partial schematic diagram in accordance with an embodiment of the present invention.

Description of a Preferred Embodiment

5

Referring to FIG. 1, a selective call radio receiver 10, e.g., a pager, comprises an antenna 11 that provides an RF carrier signal that is demodulated by the receiver 12 to provide a signal suitable for processing by the decoder 13 in a manner well known to one skilled in the art. The decoder 13 processes the recovered signal to decode the address and optional message data contained therein, and if the selective call receiver includes an optional voice output, the recovered audio components of the original signal received by the antenna 11. For selective call receivers with message storage, the recovered message or voice output is stored in the memory 14 for subsequent "playback" by an output 15. In operation, the microcomputer 16 compares information contained in the recovered signal with predetermined addresses contained in the memory 14, and when substantially similar, alerts the user that a signal has been received by alert mechanism 17. The optional output module 15 will automatically, or when manually selected by controls 18, present the message.

For a more detailed description of the structure and operation of a selective call radio paging receiver of the type shown in FIG. 1 and known to those skilled in the art, reference is made to U. S. Patent Number 4,518,961; U. S. Patent Number 4,649,538; and U. S. Patent Number 4,755,816.

Referring to FIG. 2, a display device 20 in accordance with an embodiment of the present invention comprises a display 21, e.g., a liquid crystal display (LCD), for displaying information in a manner well known to those skilled in the art. An electroluminescent panel 22 is spaced apart from the display 21 by an insulator 23. The electroluminescent panel 20 comprises a phosphorous dielectric insulating material 24 positioned between transparent electrode 25 and reflective electrode 26. The transparent electrode 25 and reflective electrode 26 are coupled to the circuitry to be described in FIG. 3 by connecting conductors thereto. The transparent electrode 25 comprises, e.g., Indium tin oxide and the reflective electrode 26 comprises, e.g., aluminum.

In operation, an alternating voltage is applied to the electrodes 25 and 26, causing the phosphorous dielectric insulating material 24 to emit light which is directed in part by the reflective electrode 26, through the display 21. Additionally, the electroluminescent panel 20 functions as a ambient light sensor in a manner to be discussed hereinafter.

Referring now to FIG. 3, the operation of the electroluminescent panel 22 may be described as comprising three modes: charging (illuminating) the electroluminescent panel 22, sensing of ambient light, and standby.

Charging circuitry 31 for charging the electroluminescent panel 22 when enabled by a clock signal 33 from the microprocessor 16 is coupled between a terminal 32 capable of receiving a supply voltage, e.g., a battery voltage, and the electroluminescent panel 22. The charging circuitry 31 comprises a PNP transistor 34 responsive to a voltage enable signal 35 from the microprocessor 16 for providing the supply voltage to coil 36. Voltage pulses from the coil 36 are supplied through the diode 37 to the electroluminescent panel 22 as determined by the disabling of transistors 38 and 39 by the clock signal 33. On alternate pulses of clock signal 33, transistors 38 and 39 are enabled for allowing current to flow through the coil 36 and discharging voltage from the electroluminescent panel 22, respectively.

Initially, during the sensing mode transistor 40 is enabled by the microprocessor 16 for discharging any voltage from the electroluminescent panel 22. Sensing circuitry 41 comprises a resistor 42 coupled between a supply voltage terminal 43 and a node 44. A diode 45 allows current through resistor 42 to the electroluminescent panel 22 in the sensing mode while blocking current in the charging mode. In the sensing mode, when the electroluminescent panel 22 is not being charged by the charging circuitry 31, the resistor 42 and capacitive electroluminescent panel 22 defines an RC time constant that provides a rising voltage at node 44. When this rising voltage reaches a threshold, transistor 46 is enabled and pulls node 47 low. This low signal at node 47 causes the microprocessor to enable the charging circuit 31.

In the standby mode, the clock signal 33 is low, the discharging signal 50 and the signal 35 are high. The state of the microprocessor signals 33, 35, 47, and 50 are illustrated for each of the three modes in the table as follows:

4

MICROPROCESSOR SIGNALS

<u>MODE</u>	<u>33</u>	<u>35</u>	<u>47</u>	<u>50</u>
CHARGING	2k HZ	L	X	L
SENSING	L	H	L/ON	H/L
			H/OFF	
STANDBY	L	H	X	H

5

where L equals low, H equals high, and X equals "don't care".

In summary, in the standby mode when a message has not been received or the user does not desire to read a message, signal 33 is low and signals 35 and 50 are high. When a message is received and is about to be read, or when it is determined by the user that a stored message should be read, the microprocessor 16 in response to the received message in the first case or in response to a user input to control 18 in the second case, will cause signal 50 to initially go high to discharge the electroluminescent panel 22 and then go low. Signal 35 goes high, signal 33 goes low, and signal 47 goes low if the selective call receiver is on and high if the selective call receiver is off. Then, if the ambient light is so low as to cause the voltage at node 47 to below the threshold, the signals 35 and 50 go low and signal 33 assumes a clock signal, e.g., 2k HZ, causing the electroluminescent panel 22 to charge and provide a backlight for the display 21.

10

15

20

CLAIMS

1. A display, comprising:
display means for displaying information; and
5 an electroluminescent panel located contiguous to the display means for sensing ambient light and lighting the display means when the ambient light is below a threshold.
2. The display according to claim 1, wherein the electroluminescent
10 panel comprises:
first and second electrodes; and
a phosphorus dielectric insulation material located between the first and second electrodes.
- 15 3. The display according to claim 1, further comprising:
current means coupled to the electroluminescent panel for providing a charge thereto;
a resistor coupled between a first supply voltage and the electroluminescent panel; and
20 a microprocessor coupled to a first node between the electroluminescent panel and the resistor for sensing a voltage indicating the level of ambient light on the electroluminescent panel and coupled to the current means for enabling the charging of the electroluminescent panel in response to the voltage being below a predetermined level.
25
4. The display according to claim 3, wherein the current means comprises:
an inductor having a first terminal coupled to the first node, and
a second terminal;
30 a first transistor having current carrying electrodes coupled between a supply voltage terminal and the second terminal of the inductor, and a control electrode coupled to the microprocessor;
a second transistor having current carrying electrodes coupled between the first node and a second supply voltage terminal, and a control
35 electrode coupled to the microprocessor; and
a third transistor having current carrying electrodes coupled between the first node and the second supply voltage terminal, and a control electrode coupled to the microprocessor.

5. The display according to claim 4, further comprising:
a fourth transistor having current carrying electrodes coupled
between a second node and the second supply voltage terminal, and a
5 control electrode coupled to the first node, the second node coupled to the
first supply voltage terminal and the microprocessor.

6. In a selective call receiver for displaying information on a display,
a method comprising the steps of:
10 displaying the information;
sensing ambient light by a electroluminescent panel located
contiguous to the display; and
lighting the display with the electroluminescent panel when the
ambient light is below a threshold.

15 7. A selective call receiver comprising:
receiver means for receiving a signal comprising information;
display means coupled to the receiver means for displaying the
information; and
20 an electroluminescent panel located contiguous to the display
means for sensing ambient light and lighting the display means when the
ambient light is below a threshold.

8. The display according to claim 7, wherein the electroluminescent
25 panel comprises:
first and second electrodes; and
a phosphorus dielectric insulation material located between the
first and second electrodes.

30 9. The display according to claim 7, further comprising:
current means coupled to the electroluminescent panel for
providing a charge thereto;
a resistor coupled between a first supply voltage and the
electroluminescent panel; and
35 a microprocessor coupled to a first node between the
electroluminescent panel and the resistor for sensing a voltage indicating
the level of ambient light on the electroluminescent panel and coupled to

the current means for enabling the charging of the electroluminescent panel in response to the voltage being below a predetermined level.

10. The display according to claim 9, wherein the current means
5 comprises:

an inductor having a first terminal coupled to the first node, and a second terminal;

a first transistor having current carrying electrodes coupled between an 32 terminal and the second terminal of the inductor, and a
10 control electrode coupled to the microprocessor;



a second transistor having current carrying electrodes coupled between the first node and a second supply voltage terminal, and a control electrode coupled to the microprocessor; and

a third transistor having current carrying electrodes coupled
15 between the first node and the second supply voltage terminal, and a control electrode coupled to the microprocessor.

11. The display according to claim 10, further comprising:

a fourth transistor having current carrying electrodes coupled
20 between a second node and the second supply voltage terminal, and a control electrode coupled to the first node, the second node coupled to the first supply voltage terminal and the microprocessor.

1/2

**FIG.1****FIG.2**20




FIG.3

INTERNATIONAL SEARCH REPORT

International application No.
PC...JS93/04698

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) :G09G 3/30

US CL :340/781

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 340/767,781,784,793; 315/169.1,169.3; 358/236,254,59; 250/214 AC, 214R, 214B,208,221

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A. 4,713,659 (OYAGI) 15 December 1987 fig 2; col. 3, lines 48-68	1-2, 6-8
Y	US, A. 5,030,943 (ANGLIN) 09 July 1991 col 4, lines 8-12; col. 1, lines 12-33	1-2, 6-8
Y	US, A. 4,024,389 (KANATANI et al) 17 May 1977 fig 2; col. 1, lines 25-59.	1-2, 6-8

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be part of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

18 JULY 1993

Date of mailing of the international search report

07 SEP 1993

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer

A. AU

TOMMY P. CHIN

Facsimile No. NOT APPLICABLE

Telephone No. (703) 305-4700

SUPERVISORY PATENT EXAMINER
GROUP 2600

INTERNATIONAL SEARCH REPORT

International application No.

P US93/04698

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A. 2,858,363 (KAZAN) 28 October 1958	1-11
A	US, A. 2,792,447 (KAZAN) 14 May 1957	1-11
A	US, A. 3,566,014 (NOREM) 23 February 1971	1-11
A	US, A. 4,50,0173 (LEIBOWITZ et al) 19 February 1985	1-11
A	US, A. 4,561,044 (OGURA et al) 24 December 1985	1-11
A	US, A. 4,562,478 (HIRASAWA et al) 31 December 1985	1-11
A	US, A. 4,809,078 (YABE et al) 28 February 1989	1-11

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.